



## ► Series 3510 Overlaminates

### Gloss Economy Calendered Overlaminates Pressure-Sensitive Film

Series 3510 is a 3.2-mil (80 micron) calendered film with a clear, permanent pressure-sensitive adhesive. Designed to protect your printed image, Series 3510 is made of a monomeric facestock and available in a gloss finish. Series 3510 is rated for outdoor durability of 3 years.

#### APPLICATIONS & FEATURES

- Protective overlaminates for all promotional calendered products
- Short-term signage, kiosks and POP displays
- Ideal for interior and exterior applications on flat surfaces
- Arlon overlaminates film is designed to be laminated cold without any heat

#### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	70 to 90 Gloss Units	
<b>THICKNESS</b>	Micrometer, Federal Bench Type	3.2-mil (80 micron)	
<b>TENSILE STRENGTH</b>	Tensile Tester with 2-in (51 mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s), web direction	≥ 15 lb/in	≥ 2.68 kg/cm
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 250%	
<b>SHELF LIFE (IN BOX)</b>	Ideal Storage Temperature 70°F (21°C) and 50% relative humidity	1 year from factory shipment	
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	50°F to 90°F	10°C to 32°C
<b>SERVICE TEMPERATURE RANGE</b>	Film applied to etched aluminum panels 24 hours prior to testing	-20°F to 150°F	-29°C to 65°C
<b>DIMENSIONAL STABILITY</b>	158°F (70°C), 48 hours, on aluminum panel	5-mil	0.13 mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min, 70°F (21°C)	≥ 1.5 lb/in	≥ 0.27 kg/cm
	PSTC-1, 24 hrs, 70°F (21°C)	10.7N/.98in	10.7N 25/mm
<b>LINER RELEASE</b>	TLMI Release at 90°, 300 in/min (760 cm/min)	125 g/2 in	24.6 g/cm




Standard Terms & Conditions Apply







## TERMS & CONDITIONS

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

June 2016

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK

 800 232 7161/+1 714 985 6300  800 329 2756  
 +31 70 354 4311  +31 70 355 7721  
 +44 161 884 0592  +31 70 355 7721

arlon.com